

DataSheet CTG EV LFP 48V 80Ah



The **CTG EV Battery** Pack is engineered for electric vehicle applications, delivering high energy density, stable performance, and long service life.

Each pack is built with premium **3.2V LFP** (Lithium Ferro Phosphate) lithium-ion cells in a **15S configuration**, forming a **48V** battery system managed by an intelligent BMS (Battery Management System).



The integrated **Smart BMS** ensures reliable operation and provides protection against over-charge, over-discharge, over-current, and short-circuit conditions—ensuring safe and efficient power delivery for various EV applications.

Features:

- 15S LFP Li-ion configuration
- Compact and lightweight design
- Smart BMS
- Easy installation
- Mobile monitoring













www.ctgeyil.com







ITEM	SPECIFICATION
Configuration	15S1P
Nominal Voltage(V)	48V
Nominal Capacity(AH)	80Ah
Operating Voltage(V)	42V - 54.75V
Rated energy(KWH)	3.84kW
Std. Charge Current	0.3C
Std. Discharge Current	1C
Max Charge Current	1C
Max Discharge Current	3C
Weight (Approx. in Kg)	40Kg
IP grade	IP 65
Dimensions (LxWxH)	478*272*200
Cycle Life	3500 Cycle (90% DOD)
Warranty	5 Years (Refer CTG Warranty Document)
Working Temperature	0°C to 55°C (Charging) /-20° to +60°C (Discharging)
Recommended Charger	LFP 54.75V / 24A

