

## DataSheet CTG EV LFP 51.2V 160Ah



The CTG EV Battery Pack is engineered for electric vehicle applications, delivering high energy density, stable performance, and long service life.

Each pack is built with premium 3.2V LFP (Lithium Phosphate) lithium-ion cells **16S** Ferro configuration, forming a 51.2V system battery intelligent (Battery managed by **BMS** an Management System).



The integrated **Smart BMS** ensures reliable operation and provides protection against over-charge, over-discharge, over-current, and short-circuit conditions-ensuring safe and efficient power delivery for various EV applications.

## **Features:**

- 16S LFP Li-ion configuration
- · Compact and lightweight design
- Smart BMS
- Easy installation
- Mobile monitoring











High Easy Efficiency Installation

Expandable system

**Smart BMS** 

www.ctgeyil.com





ITEM	SPECIFICATION
Configuration	16S2P
Nominal Voltage(V)	51.2V
Nominal Capacity(AH)	160Ah
Operating Voltage(V)	44.8V - 58.4V
Rated energy(KWH)	8.19kW
Std. Charge Current	0.3C
Std. Discharge Current	1C
Max Charge Current	1C
Max Discharge Current	3C
Weight (Approx. in Kg)	48Kg
IP grade	IP 65
Dimensions (LxWxH)	340*510*268
Cycle Life	3500 Cycle (90% DOD)
Warranty	5 Years (Refer CTG Warranty Document)
Working Temperature	0°C to 55°C (Charging) /-20° to +60°C (Discharging)
Recommended Charger	LFP 58.4V / 48A

