

DataSheet CTG EV LFP 73.6V 60Ah



The **CTG EV Battery** Pack is engineered for electric vehicle applications, delivering high energy density, stable performance, and long service life.

Each pack is built with premium **3.2V LFP** (Lithium Ferro Phosphate) lithium-ion cells in a **23S configuration**, forming a **73.6V 60Ah** battery system managed by an intelligent BMS (Battery Management System).



The integrated **Smart BMS** ensures reliable operation and provides protection against over-charge, over-discharge, over-current, and short-circuit conditions—ensuring safe and efficient power delivery for various EV applications.

Features:

- 23S LFP Li-ion configuration
- Compact and lightweight design
- Smart BMS
- Easy installation
- Mobile monitoring







Easy Installation



Expandable system



Smart BMS

www.ctgeyil.com





ITEM	SPECIFICATION
Configuration	23S10P
Nominal Voltage(V)	73.6V
Nominal Capacity(AH)	60Ah
Operating Voltage(V)	62V - 83.95V
Rated energy(KWH)	4.42kW
Std. Charge Current	0.3C
Std. Discharge Current	1C
Max Charge Current	1C
Max Discharge Current	3C
Weight (Approx. in Kg)	39.1Kg
IP grade	IP 65
Dimensions (LxWxH)	210*161*280
Cycle Life	2000 Cycle (90% DOD)
Warranty	3 Years (Refer CTG Warranty Document)
Working Temperature	0°C to 55°C (Charging) /-20° to +60°C (Discharging)
Recommended Charger	LFP 83.95V/18A

